

FULL HD NVR




Onvif



FULL HD



2020-Q4



سایر برتری‌ها:

- امکان گسترش نرم افزاری به درخواست مصرف کنندگان
- نرم افزارهای موبایل و ویندوز حرفه ای به زبان فارسی و انگلیسی
- استفاده از CPU و Ram بیشتر نسبت به سایر برندها
- بالاترین سطح پشتیبانی از دوربین های سایر برندها
- پشتیبانی از دوربین های ۵ مگا پیکسلی
- سیستم عامل به زبان فارسی و انگلیسی
- وب نویسی به زبان فارسی و انگلیسی

پشتیبانی از قابلیت‌های هوشمند:

- عبور از خط
- فنس مجازی
- ورود به منطقه
- خروج از منطقه
- کم شدن اشیاء
- اضافه شدن اشیاء
- تشخیص حرکت
- تشخیص چهره
- جستجوی هوشمند تصاویر
- تشخیص حرکت سریع افراد
- تشخیص پوشاندن دوربین

3 years

Platinum Guarantee

- سه سال گارانتی پلاتینیوم بدون قید و شرط کی دی تی شامل:

- آبخوردگی، شکستگی، ضربه دیدگی، خسارت ناشی از صاعقه، زنگ زدگی، نوسانات برق و سایر اتفاقات و خدمات

CPU & Capabilities

CPU	ARM Cortex-A7@850MHz
IP Channel Input	8CH x 30fps (Up to 5MP Supported)

Video & Audio

HDMI Output	1CH x Full HD (1920 x 1080)
VGA Output	1CH x Full HD (1920 x 1080)
Audio Input/ Output	N/A

Recording

Video Compression	H.264+(Ultra H.264), H.265+ (Ultra H.265) Smart Event Codec
Audio Compression	G.711A, G.711U
Video Resolution	5MP, 4MP, 3MP, 1080P, 720P, CIF, QCIF, D1
Input Bandwidth	40 Mbps
Record Mode	Manual, Schedule, Alarm, Event, Smart Event
Pre & Post Record	Pre 1~30 sec, Post 10~300 sec

Playback & Backup

Sync Playback	4CH x 2MP@30fps Resolution / 1CH x 5MP@30fps Resolution
Search Mode	Time & Date, Motion, Alarm Input, All Smart Function
Playback Mode	Normal, Time Division, Label, Event, Picture Playback, Smart Playback
Backup Mode	USB Device, Network, Internal Sata Burner

Network & Monitoring

Protocols	HTTPS, HTTP, TCP/IP V4-V6, ICMP, RTSP, UDP, NTP, DHCP, DDNS, FTP, SNMP-V1-V2-V3, UPNP, P2P, NAT, Multi Cast
Compatibility	Onvif Ver2.6, Profile S, CGI, SDK, API
Output Bandwidth	20 Mbps
User	10 Users
Streaming Method	Unicast, Multicast
Web Viewer	Internet Explorer
Windows Software	Unlimited KDT CMS 128CH Per Monitor
Smart Device	IOS, Android Phone & Tablet

Hard Disk

HDD	1 Sata HDD
Capacity	Up to 10TB Capacity For Each HDD
Raid Support	N/A
Group HDD	N/A

External Interface

Network	1 x RJ45(10/100mbps)+LED Indicator
Wifi / 4G Dongle	Supported
USB Interface	2 x USB 2.0
eSATA	N/A
Alarm In / Alarm Out	N/A
Controller	N/A

Smart Function

Intelligent Function	11 Smart Function Line Crossing, Area Intrusion, Face Detection, Unattended Objects, Object Missing, Region Entrance, Region Exiting, Fast Moving, Video Shelter, Motion Detection, Smart Playback.
----------------------	--

General

Power Supply	DC12V - 4A
Power Consumption	≤10 W Without HDD
Working Environment	-20°C ~ +65°C / 10% ~ 90% RH (Non condensing)
Rackmount	N/A
Dimension (WxDxH)	246*230*45 mm
Weight/g	1.5 Kg

Guarantee

Product Guarantee	3 Years Platinum Guarantee
MTBF	100K hrs min. MIL-HDBK-217F (25°)