



**2 years  
Silver  
Guarantee**

- دو سال گارانتی نقره‌ای بدون قید و شرط کی دی تی
- سه سال ضمانت پایداری کیفیت تصویر

#### سایر برتری‌ها:

- بدنه ضد آب و گرد و غبار با درجه IP67
- سرور انتقال تصویر در ایران
- پشتیبانی از H.264+ / H.265+
- پشتیبانی از ONVIF ورژن 2.6
- قابلیت دید در شب هوشمند

#### قابلیت‌های هوشمند:

- عبور از خط
- فنس مجازی
- تشخیص حرکت سریع افراد
- تشخیص حرکت
- پوشاندن تصاویر
- کم شدن اشیاء
- اضافه شدن اشیاء

Camera	
Image Sensor	<b>2MP</b> Cmos Sensor (1/2.9")
CPU	<b>ARM Cortex-A7@600MHz</b>
Lens	<b>3.6mm Fixed</b> Lens
Resolution	1920*1080 ( <b>2MP</b> )
Available IR Range	<b>30~35M Smart</b> IR SMD Technology
D/N Filter	IR Cut Filter Switch (ICR)
Min Illumination	Color: <b>0.01</b> Lux(AGC on) - B/W: 0.0 Lux(IR on)
Angle of View	<b>H-FOV: 74° , V-FOV: 58° , D-FOV: 88°</b>
StarLight View	N/A
Picture Adjust	
Picture Function	<b>DWDR, BLC, HLC, Defog</b>
Shutter Speed	Manual (1/3 ~ 1/10.000), Auto
Image Parameter Control	Off, On, Timing (Adjust 0 ~ 255)
D/N Control	Timing, Auto, Color on, Color off
Image Parameter	Saturation, Brightness, Contrast, Sharpness, Hue
Video / Audio	
Video Compression	H.264+(Ultra H.264), H.265+ ( <b>Ultra H.265</b> ) <b>Smart Event Codec</b>
Audio Compression	N/A
Frame Rate(60Hz)	30fps@960P, <b>25fps@1080P</b>
Transmission Stream	Dual Stream (code rate:128Kb~10mb)
Network	
Protocols	HTTPS, HTTP, <b>TCP/IP V4-V6</b> , ICMP, RTSP, UDP, NTP, DHCP, DDNS, FTP, SNMP-V1-V2-V3, UPNP, <b>P2P</b> , NAT, Multi Cast, <b>IGMP</b>
Compatibility	<b>Onvif Ver2.6</b> , Profile S, CGI, SDK, API
Max Users	10 Users
Streaming Method	Unicast, Multicast
Web Viewer	Internet Explorer
Recording Software	Unlimited KDT CMS/VMS 128CH Per Monitor
Smart Device	IOS, Android Phone & Tablet

Function	
Recording	FTP, NVR, CMS, NAS
Record Type	Manual, Motion Detection, Smart Detection, Schedule
Alarm Triggers	All Intelligent Function
Event Action	Email, PTZ, Snapshot, Recording, Buzzer, Pop up, Show Message
Intelligent Function	<b>7 Smart Function</b> Line Crossing, Area Intrusion, Fast Moving, Unattended Object, Object Missing, Motion Detection, Video Shelter
Interface	
Network	RJ45(10/100mbps)
Audio	N/A
Alarm	N/A
CVBS	N/A
Power	<b>PoE</b> LAN, DC In
Control	N/A
Memory Slot	N/A
General	
IP Rating	<b>IP67</b>
Lens Cover	<b>Nano Glass</b>
Power Supply	DC12V ± 25%
POE Supply	<b>IEEE802.3af - Max 7.1W</b>
Web Language	English, <b>Persian</b>
Dimension	153*65 mm
Weight	287 g
Operation Humidity	Max Up to 95%RH(Non Condensing)
Operation Temp	-45°C ~ +75°C
Guarantee	
Product Guarantee	2 Years Silver Guarantee
MTBF	100K hrs min. MIL-HDBK-217F (25°)