


قابلیت رایبه فرم و امنیتی جهت استفاده در مراکز فوق حساس و نظامی - فاقد قابلیت دسترسی از طریق اینترنت



E801



1401-S3

2 years
Silver
Guarantee

- دو سال گارانتی نقره‌ای بدون قید و شرط کی دی تی
- سه سال ضمانت پایداری کیفیت تصویر

سایر برتری‌ها:

- بدنه ضد آب و گرد و غبار با درجه IP67
- سرور انتقال تصویر در ایران
- پشتیبانی از H.264+ / H.265+
- پشتیبانی از ONVIF ورژن 2.6
- قابلیت دید در شب هوشمند

Camera	
Image Sensor	5MP Progressive scan Cmos Sensor (1/2.7")
CPU	Single-Core ARM Cortex-A7@750MHz
Lens	3.6 mm Fixed Lens @F2.0 (2.8 mm Optional)
Resolution	2592×1944 (5MP)
Available IR Range	30~40 m Smart IR SMD (Array) Technology
D/N Filter	IR cut filter with auto switch
Min Illumination	Color: 0.01 Lux(AGC on) - B/W: 0.0 Lux(IR on)
Angle of View	H-FOV: 82°-(94°), V-FOV: 43°-(69°), D-FOV: 92°-(119°)
StarLight View	N/A
Picture Adjust	
Picture Function	DWDR, 2D/3D DNR, BLC, HLC
Shutter Speed	Manual (1/3 ~ 1/10.000), Auto
Image Parameter Control	Off, On, Timing (Adjust 0 ~ 255)
D/N Control	Timing, Auto, Color on, Color off
S/N	> 52dB
Image Parameter	Saturation, Brightness, Contrast, Sharpness, Hue
Video / Audio	
Video Compression	H.264+(Ultra H.264), H.265+ (Ultra H.265)
Audio Compression	N/A
Frame Rate(60Hz)	20fps@ 5MP, 25fps@ 4MP, 30fps@ 2MP
Transmission Stream	Triple Stream (Video Bit Rate:11 Kbps~10 Mbps)
Network	
Protocols	TCP/IP, ICMP, HTTP, HTTPS, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, UPnP-TM, P2P, Bonjour, IPV6, RTMP, NAT
Compatibility	Onvif Ver2.6, Profile S, CGI, SDK, API
Streaming Method	Unicast, Multicast
Web Viewer	Internet Explorer
Smart Device	IOS, Android Phone & Tablet

Function	
Recording	NVR, CMS, VMS
Record Type	Manual, Motion Detection, Smart Detection, Schedule
Alarm Triggers	N/A
Event Action	Email, PTZ, Snapshot, Recording, Buzzer, Pop up, Show Message
Event	Smart Motion Detection, Video Shelter
Intelligent Function	N/A
Interface	
Network	1 RJ45 (10M / 100M) Ethernet Port
Audio	N/A
Alarm	N/A
CVBS	N/A
Power	PoE LAN, DC In
Control	N/A
Memory Slot	N/A
General	
IP Rating	IP67, 2KV Surge Protection
Power Supply	DC12V ± 10%
POE Supply	IEEE802.3af - Max 6.5 Watt
Web Language	English, Persian
Dimension	90*89 mm
Weight	230 g
Operation Humidity	Humidity 95% or less (non-condensing)
Operation Temp	-30°C ~ +60°C
Guarantee	
Product Guarantee	2 Years Silver Guarantee
MTBF	100K hrs min- MIL-HDBK-217F (25°)
Certificates	EN, CN, FCC, CFR