



## سایر برتری‌ها:

- پشتیبانی از میکرو SD با ظرفیت 128GB
- بدنه ضد آب و گرد و غبار با درجه IP67
- پشتیبانی از H.264+ / H.265+
- پشتیبانی از ONVIF ورژن 2.6
- قابلیت دید در شب هوشمند
- قابلیت WDR, BLC, HLC, Defog و ROI تا ۸ ناحیه

**2 years  
Silver  
Guarantee**

- دو سال گارانتی نقره‌ای بدون قید و شرط کی دی تی
- سه سال ضمانت پایداری کیفیت تصویر



1401-S3

Camera	
Image Sensor	<b>2MP (Sony-Japan)</b> Progressive scan Cmos Sensor (1/2.9")
Case Size	<b>7"</b>
CPU	<b>Dual-Core ARM Cortex-A7@900 MHz</b>
Lens	<b>33X Optical Lens (5.3~175 mm) (F-Stop F1.6~F5.8)</b>
Resolution	1920*1080 (2MP)
Available IR Range	<b>150~160 m</b> Smart IR SMD Technology
D/N Filter	IR Cut Filter Switch (ICR)
Min Illumination	Color: <b>0.002 Lux</b> (AGC on) - B/W: 0.0 Lux(IR on)
PTZ	<b>Pan Range:</b> 360° Endless - <b>Pan Speed:</b> 0.1~240°/S <b>Tilt Range:</b> -10°~100° - <b>Tilt Speed:</b> 0.1~180°/S <b>Number of Preset:</b> 255 - <b>Patrol:</b> 4 - <b>Pattern:</b> 8 - Park Action: Yes
StarLight View	Yes-Color
Picture Adjust	
Picture Function	<b>120 db WDR/DWDR, 2D/3D DNR, BLC, HLC, ROI, Defog</b>
Shutter Speed	Manual (1/3 ~ 1/10.000), Auto
Image Control	Off, On, Timing (Adjust 0 ~ 255)
D/N Control	Timing, Auto, Color on, Color off
Image Setting	Saturation, Brightness, Contrast, Sharpness, Hue
Video / Audio	
Video Compression	H.264, H.264+, H.265, H.265+
Audio Compression	G.711A, G.711U
Frame Rate(60Hz)	<b>30fps@ 2MP(1920*1080)</b> , 30fps@ 960P
Transmission Stream	<b>Triple Stream</b> (Code Rate: 128kb-10mb)
Network	
Protocols	HTTPs, HTTP, <b>TCP/IP V4-V6</b> , ICMP, RTSP, UDP, NTP, DHCP, DDNS, FTP, SNMP-V1-V2-V3, Multi Cast
Compatibility	<b>Onvif Ver2.4</b> , Profile S, CGI, SDK, API
Streaming Method	Unicast, Multicast
Web Viewer	Internet Explorer
Smart Device	IOS, Android Phone & Tablet

Function	
Recording	FTP, NVR, CMS,VMS, SD Card
Record Type	Manual, Motion Detection, Smart Detection, Schedule
Alarm Triggers	N/A
Event Action	Email, PTZ, Snapshot, Recording, Alarm Out
Event	Motion Detection, Video Shelter
Intelligent Function	N/A
Interface	
Network	RJ45(10/100Mbps)
Audio	Audio Out, Audio In
Alarm	Alarm Out, Alarm In
CVBS	Yes
Power	<b>PoE</b> LAN, DC In
Reset Button	Yes ( <b>Optional</b> )
Memory Slot	Yes - Micro SD/SDHC/SDXC Slot ( <b>128 Gb Max</b> )
General	
IP Rating	<b>IP67, 3KV Surge Protection</b>
Power Supply	AC24 V ± 25% (3A Max)
POE Supply	<b>IEEE802.3at-af-Max 25 Watt</b>
Web Language	English, <b>Persian</b>
Dimension	336*227 mm
Weight	6.5 kg
Operation Humidity	Max Up to 95%RH(Non Condensing)
Operation Temp	-40°C ~ +70°C
Guarantee	
Product Guarantee	2 Years Silver Guarantee
MTBF	100K hrs min. MIL-HDBK-217F (25°)
Certificates	EN, CN, FCC, CFR