



1402-S1

**2 years Silver Guarantee**

- دو سال گارانتی نقره‌ای بدون قید و شرط کی دی تی
- سه سال ضمانت پایداری کیفیت تصویر

- پشتیبانی از میکرو SD با ظرفیت 128GB
- بدنه ضد آب و گرد و غبار با درجه IP67
- پشتیبانی از H.264+ / H.265+
- پشتیبانی از ONVIF ورژن 2.6
- قابلیت دید در شب هوشمند
- قابلیت WDR, BLC, HLC, Defog و ROI تا ۸ ناحیه

Camera	
Image Sensor	2MP Super Starlight (Sony-Japan) Cmos Sensor (1/1.9")
Case Size	8"
CPU	Dual-Core ARM Cortex-A7@900MHZ
Lens	38X Optical Lens (4.6~174 mm) (F-Stop F1.2~F5.8)
Resolution	1920*1080 (2MP)
Available IR Range	500 m Smart Optical Laser IR SMD Technology
D/N Filter	IR Cut Filter Switch (ICR)
Min Illumination	Color: 0.001 Lux(AGC on) - B/W: 0.0 Lux(IR on)
PTZ	Pan Range: 360° Endless - Pan Speed: 0.1°~240°/S Tilt Range: -10°~100° - Tilt Speed: 0.1°~180°/S Number of Preset: 255 - Patrol: 4 - Pattern: 8 - Park Action: Yes
Night Vision	Color /IR
Picture Adjust	
Picture Function	120 db WDR, DWDR, BLC, HLC, Defog, ROI
DIS	Yes
Digital Zoom	16X
Shutter Speed	Manual (1/3 ~ 1/100.000), Auto
Image Control	Off, On, Timing (Adjust 0 ~ 255)
D/N Control	Timing, Auto, Color on, Color off
Image Setting	Saturation, Brightness, Contrast, Sharpness, Hue
Video / Audio	
Video Compression	H.264+(Ultra H.264), H.265+ (Ultra H.265)
Audio Compression	G.711A, G.711U
Frame Rate(60Hz)	30fps@1080P
Transmission Stream	Triple Stream (Code Rate: 128kbps-16mbps)
Network	
Protocols	HTTPS, HTTP, TCP/IP V4-V6, ICMP, RTSP, UDP, NTP, DHCP, DDNS, FTP, SNMP-V1-V2-V3, Multi Cast
Compatibility	Onvif Ver2.4, Profile S, CGI, SDK, API
Streaming Method	Unicast, Multicast
Web Viewer	Internet Explorer

Function	
Recording	FTP, NVR, CMS,VMS, SD Card
Record Type	Manual, Motion Detection, Smart Detection, Schedule
Alarm Triggers	N/A
Event Action	Email, PTZ, Snapshot, Recording, Alarm Out
Event	Motion Detection, Video Shelter
Intelligent Function	N/A
Interface	
Network	RJ45(10/100mbps)
Audio	N/A
Alarm	N/A
CVBS	N/A
Power	PoE LAN, DC/AC In
Reset Button	N/A
Memory Slot	Yes - Micro SD/SDHC/SDXC Slot (128 Gb Max)
General	
IP Rating	IP67, IK10, 3KV Surge Protection
Power Supply	AC12 V ± 25% (4A Max)
POE Supply	IEEE802.3at-af-Max 25 Watt
Web Language	English, Persian
Dimension	335*237 mm
Weight	8.5 kg (with package)
Operation Humidity	Max Up to 95%RH(Non Condensing)
Operation Temp	-40°C ~ +70°C
Guarantee	
Product Guarantee	2 Years Silver Guarantee
MTBF	100K hrs min- MIL-HDBK-217F (25°)