Fiber Optic Equipment

PG-150CMSC



Pigtail		
Cable Type	Fiber Optic Pigtail SC/UPC	
Color	Blue	
Count Core	1 Core	
Material	Flame PVC Outer Jacket	
Mode	Single Mode	
Temperature	-40C~+70C	
Core Size	0.9 mm	
Strip Size	1.5 M	
Insertion Loss	0.28DB	
Return Loss	55-8DB	











-
SC
\mathbf{J}



Duplex Adapter	
Cable Type	Fiber Optic SC to SC Adapter
Color	Blue
Count Core	2 Core
Material	Material Flame PVC Outer Jacket
Mode	Single Mode UPC Duplex Couplers
Temperature	-40C~+70C
Connector	SC Female to SC Female Fiber Coupler are Lightweight Due to Their Plastic
Ability	Fiber Optic Cable to Cable Connection or Patch Cords Extender in Local Area Networks (LANS), Wide Area Networks (WAN), Metropolitan Area Networks (MAN) Data Center, Business, Premises, Security, FTTH, FTTP, FTTA, High EMI, and Commercial Applications. SC-SC Fiber Adapter Duplex Comply with IEC 61754-4, IEC 60784-14 and TIA 604-3 and Conform to RoHS Standards.

TC-60

