

NS-3U 8P 6UTP



UTP Socket	
Applicable Standards	T568A / T568B
Type	UTP - Cat6
Contact Resistance	20m ohms
Insulation Resistance	100M ohms
Temperature Rating (Min / Max)	-40/80 °C
Weight	3.4g / pcs
Wire Awg Min / Max (Solid / Stranded)	24AWG to 23AWG
Conductor Diameter (Min/Max)	0.40/0.55mm
Cord Diameter (Max)	1.3mm
Finished	03MU Micro-Inch Gold Plating
Material	PVC

NS-3U 8P 6SFTP



SFTP Socket	
Applicable Standards	T568A / T568B
Type	SFTP - Cat6
Contact Resistance	20m ohms
Insulation Resistance	100M ohms
Temperature Rating (Min / Max)	-40/80 °C
Weight	6.8g / pcs
Wire Awg Min / Max (Solid / Stranded)	24AWG to 23AWG
Conductor Diameter (Min/Max)	0.40/0.55mm
Cord Diameter (Max)	1.5mm
Finished	03MU Micro-Inch Gold Plating
Material	Metal

NS-3U 8P 6SFTPS



SFTP Socket	
Applicable Standards	T568A / T568B
Type	SFTP - Cat6
Contact Resistance	20m ohms
Insulation Resistance	100M ohms
Temperature Rating (Min / Max)	-40/80 °C
Weight	10.8g / pcs
Wire Awg Min / Max (Solid / Stranded)	24AWG to 23AWG
Conductor Diameter (Min/Max)	0.40/0.55mm
Cord Diameter (Max)	1.7mm
Finished	03MU Micro-Inch Gold Plating
Material	Metal
Load Bar	PVC(With Guide)
Strain Relief	Metal

NS-3U 8P 7SFTPS



SFTP Socket	
Applicable Standards	T568A / T568B
Type	SFTP - Cat7
Contact Resistance	20m ohms
Insulation Resistance	100M ohms
Temperature Rating (Min / Max)	-40/80 °C
Weight	11.2g / pcs
Wire Awg Min / Max (Solid / Stranded)	24AWG to 23AWG
Conductor Diameter (Min/Max)	0.40/0.55mm
Cord Diameter (Max)	2.1mm
Finished	03MU Micro-Inch Gold Plating
Material	Metal
Load Bar	PVC(With Guide)
Strain Relief	Metal



1403-S1