



white Light



1402-S1

2 years Silver Guarantee

- دو سال گارانتی نقره‌ای بدون قید و شرط کی دی تی
- سه سال ضمانت پایداری کیفیت تصویر

سایر برتری‌ها:

- پشتیبانی از میکرو SD با ظرفیت 256Gb
- بدنه ضد آب و گرد و غبار با درجه IP67
- سرور انتقال تصویر در ایران
- پشتیبانی از H.264+ / H.265+
- پشتیبانی از ONVIF ورژن 2.6
- قابلیت دید در شب هوشمند
- قابلیت WDR, BLC, HLC, Defog
- پشتیبانی از ضبط اضطراری ANR

قابلیت‌های هوشمند:

- عبور از خط
- فنس مجازی
- ورود به منطقه
- خروج از منطقه
- گم شدن اشیاء
- اضافه شدن اشیاء
- تردد شمار افراد
- تشخیص انسان
- تشخیص حرکت سریع افراد
- تشخیص تغییر زاویه دوربین
- تشخیص پارک غیر مجاز خودرو
- تشخیص پرسه زنی افراد
- تشخیص صدای غیر عادی
- تشخیص عدم فکوس لنز
- تشخیص تجمع افراد

| Camera | |
|-------------------------|--|
| Image Sensor | 8MP Progressive scan Cmos Sensor (1/2.8") |
| CPU | Dual-Core ARM Cortex-A7@900 MHz |
| Lens | 2.8 mm Fixed Lens @F1.6 |
| Resolution | 3840*2160 (8MP) |
| Available IR Range | 30~40 m Smart IR SMD Technology Smart White light Technology |
| D/N Filter | IR cut filter with auto switch |
| Min Illumination | Color: 0.01 lux(AGC on) - B/W: 0.0 Lux(IR on) |
| Angle of View | H-FOV: 114°, V-FOV: 66°, D-FOV: 127° |
| Night Vision | Color /IR |
| Picture Adjust | |
| Picture Function | WDR/DWDR, BLC, HLC, Defog, ROI, Rotate |
| Shutter Speed | Manual (1/3 ~ 1/10.000), Auto |
| Image Parameter Control | Off, On, Timing (Adjust 0 ~ 255) |
| D/N Control | Timing, Auto, Color on, Color off |
| S/N | > 52dB |
| Image Parameter | Saturation, Brightness, Contrast, Sharpness, Hue |
| Video / Audio | |
| Video Compression | H.264+(Ultra H.264), H.265+ (Ultra H.265) |
| Audio Compression | G.711A, G.711U |
| Frame Rate(60Hz) | 15fps@ 8MP (3840*2160), 15fps@ 6MP, 30fps@ 4MP, 30fps@ 2MP |
| Transmission Stream | Triple Stream (Video Bit Rate:11 Kbps~8 Mbps) |
| Network | |
| Protocols | TCP/IP(v4, v6), ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, IGMP, UPnP, SMTP, UPnP-TM, P2P, Bonjour, SNMP (v1, v2, v3), UDP, NAT, Multicast |
| Compatibility | Onvif Ver.2.6, Profile S, CGI, SDK, API |
| Streaming Method | Unicast, Multicast |
| Web Viewer | Internet Explorer |
| Smart Device | IOS, Android Phone & Tablet |

| Function | |
|----------------------|--|
| Recording | FTP, NVR, CMS, VMS, NAS, SD Card, ANR |
| Record Type | Manual, Motion Detection, Smart Detection, Schedule |
| Alarm Triggers | All Intelligent Function |
| Event Action | Email, PTZ, Snapshot, Recording, Buzzer, Pop up, Show Message, Smart Light |
| Event | Motion Detection, Video Shelter |
| Intelligent Function | 15 Smart Function Line Crossing, Area Intrusion, Unattended Object, Object Missing, Region Entrance, Region Exiting, Fast Moving, Loitering Detection, People Gathering Detection, Parking Detection, Blurred Detection, Scene Change Detection, Audio exception Detection, Crossing Line Statistics, Human Detection |
| Interface | |
| Network | 1 RJ45 (10M / 100M) Ethernet Port |
| Audio | Audio In, Audio Out |
| Alarm | N/A |
| CVBS | N/A |
| Power | PoE LAN, DC In |
| Reset Button | Yes (Optional) |
| Memory Slot | Yes - Micro SD/SDHC/SDXC Slot (256 Gb Max) (ANR Support) |
| General | |
| IP Rating | IP67, 2KV Surge Protection |
| Power Supply | DC12V ± 10% |
| POE Supply | IEEE802.3af - Max 6 Watt |
| Web Language | English, Persian |
| Dimension | 103*84 mm |
| Weight | 380 g |
| Operation Humidity | Humidity 95% or less (non-condensing) |
| Operation Temp | -30°C ~ +60°C |
| Guarantee | |
| Product Guarantee | 2 Years Silver Guarantee |
| MTBF | 100K hrs min- MIL-HDBK-217F (25°) |
| Certificates | EN, CN, FCC, CFR |