

KB-P1-W

Wired PIR



Software features	
Arm modes	Away/Stay
Hardware features	
Type	Wired
Power	DC 10v~15v
Sensor	IR
Electrical characteristics	
Working Current	≤150uA(Static current), ≤30mA(Alarm current)
Operation temperature	-20 °C to +60 °C
Transmitted power	10mW
Display	
LEDs status	Alarm, Fault, Battery low
General	
Dimension(WxHxD)	130mm*64mm*43mm , ±1mm
material	Plastic
Color	White
Installation Height	2~2.2m
Weight	86.5 g
Detective Angle	110°C
Detective Distance	12m

KB-P1-WL

Wireless PIR



Software features	
Arm modes	Away/Stay
Hardware features	
Type	Wireless RF 433Mhz
Power	DC 3V(2*CR14505)
Sensor	IR
Electrical characteristics	
Working Current	≤20mA(Static current), ≤15mA(Alarm current)
Operation temperature	-20 °C to +60 °C
Transmitted power	10mW
Wireless transmission	
RF frequency	433 Mhz
RF method	Support
Wireless security	Frequency Hoping 128 AES Encryption
Display	
LEDs status	Alarm, Fault, Battery low
General	
Dimension(WxHxD)	130mm*64mm*43mm, ±1mm
material	Plastic
Color	White
Installation Height	2~2.2m
Weight	286.5 g
Detective Angle	110°C
Detective Distance	12m

KB-R1

Remote



Remote	
Coding	Keeloq and Advanced Encryption Standard
Antenna	onboard
Frequency	433MHz
Number of Buttons	4
Buttons Combination	Yes
Functions	12
Button's Function	Customizable
Battery	27A 12v
Colors	Black, Red, Blue, Gold
Size	13*39*65mm
Distance	80 m



1403-S3