

KB-K1

Keypad



Keypad

Key Mechanism	Touch
Display	Charater 2*16
Buzzer	Yes
Adjustable Screen Light	Yes
Adjustable Buzzer Level	Yes
Keypad Wired Zone	1
Connection	Wire
Communication Protocol	RS485
Cable length	100 m(Cat 3 and More)

KB-S1-W

Wired Siren



Software features

Arm modes Alarm, Stay Arm, Away Arm, Disarm, SOS, Fault

Hardware features

Type Wired
Power DC 10v~15v

Electrical characteristics

Battery type Built in on board (18650)
Working Current ≤3mA (Static current), ≤450mA (Alarm current)
Transmitted power 10mW
Operation temperature -20 °C to +60 °C / Humidity: =95%(RH)

Display

LEDs status Alarm, Fault, Battery Low

General

Dimension (WxHxD) 320mm*215mm*110mm
material/ Color Plastic White
Weight 2.2kgs
Max. Volume 105dB (in 1 Meter)

KB-S1-WL

Wireless Siren



Software features

Arm modes Alarm, Stay Arm, Away Arm, Disarm, SOS, Fault

Hardware features

Type Wireless RF 433Mhz
Power DC3.7V-4.2V (5200mAh 3.7V 18650 lithium battery)

Electrical characteristics

Battery type Built in on board (18650)
Working Current ≤3mA (Static current), ≤450mA (Alarm current)
Transmitted power 10mW
Operation temperature -20 °C to +60 °C / Humidity: =95%(RH)

Wireless transmission

RF frequency 433 Mhz
RF method Support
Wireless security Frequency Hoping 128 AES Encryption

Display

LEDs status Alarm, Fault, Battery Low

General

Dimension (WxHxD) 320mm*215mm*110mm
material/ Color Plastic White
Weight 2.2kgs
Max. Volume 105dB (in 1 Meter)

