



Full Color



1403-S3

2 years Silver Guarantee

- دو سال گارانتی نقره‌ای بدون قید و شرط کی دی تی
- سه سال ضمانت پایداری کیفیت تصویر

سایر برتری‌ها:

- بدنه ضد آب و گرد و غبار با درجه IP67
- پشتیبانی از H.264+ / H.265 +
- پشتیبانی از ONVIF ورژن 2.4
- قابلیت WDR, BLC, HLC

Camera	
Image Sensor	3MP (Sony-Japan) Progressive scan Cmos Sensor (1/2.8") Ultra-Low-illumination
CPU	Dual-Core ARM 2 x A53@1400 MHz
Lens	5~50mm Motorized 10X Optical ZoomFast Auto Focus Lens
Resolution	2304*1296 (3MP)
Available IR Range	40~50 m White Light Technology (6 pcs White Light)
D/N Filter	Color
Min illumination	Color: 0.003 Lux (AGC on) - B/W: 0.0 Lux(White Light on)
Angle of View	H-FOV: 50°~3.6° , V-FOV: 36°~2° , D-FOV: 69°~5°
Night Vision	Full Color
Picture Adjust	
Picture Function	120dB WDR/DWDR, 2D/3D DNR, BLC, HLC
Shutter Speed	Manual (1/3 ~ 1/8.000), Auto (Image Algorithm)
Image Parameter Control	Off, On, Timing (Adjust 0 ~ 255)
D/N Control	Timing, Auto, Color on, Color off
Image Parameter	Saturation, Brightness, Contrast, Sharpness, Hue
Video / Audio	
Video Compression	H.264, H.265, MJPEG
Audio Compression	N/A
Frame Rate(60Hz)	30fps@(2304x1296)
Transmission Stream	Dual Stream (Code Rate: 128kbps-10mbps)
Network	
Protocols	RTSP/PPPOE/DHCP/DDNS/NTP/UPnP/SMTP
Compatibility	Onvif Ver2.4 , Profile S
Streaming Method	Unicast, Multicast
Web Viewer	Internet Explorer

Function	
Recording	FTP, NVR, CMS, VMS
Record Type	Manual, Motion Detection, Schedule
Alarm Triggers	N/A
Intelligent Function	N/A
Interface	
Network	1 RJ45 (10M / 100M) Ethernet Port
Audio	N/A
Alarm	N/A
CVBS	N/A
Power	PoE LAN, DC In
Reset Button	N/A
Memory Slot	N/A
General	
Protection Rating	IP67, IK10 , 6KV Surge Protection
Power Supply	DC12V ± 10%
POE Supply	IEEE802.3af - Max 11 Watt
Web Language	English
Dimension	275*102 mm
Weight	1.2 Kg
Operation Humidity	Humidity 95% or less (non-condensing)
Operation Temp	-30°C ~ +60°C
Guarantee	
Product Guarantee	2 Years Silver Guarantee
MTBF	100K hrs min. MIL-HDBK-217F (25°)
Certificates	EN, CN, FCC, CFR