



1403-S3

2 years Silver Guarantee

- دو سال گارانتی نقره‌ای بدون قید و شرط کی دی تی
- سه سال ضمانت پایداری کیفیت تصویر

سایر برتری‌ها:

- پشتیبانی از میکرو SD با ظرفیت 256GB
- بدنه ضد آب و گرد و غبار با درجه IP67
- پشتیبانی از H.264+ / H.265+
- پشتیبانی از ONVIF ورژن 2.6
- قابلیت دید در شب هوشمند
- قابلیت WDR, BLC, HLC, Defog و ROI تا 8 ناحیه

Camera	
Image Sensor	2MP (Sony-Japan) Progressive scan Cmos Sensor (1/2.8")
CPU	Dual-Core ARM 2 x A53@1400 MHz
Lens	7~22mm Motorized 3X Optical Zoom(F-Stop F1.6~F2.8) Fast Auto Focus Lens
Resolution	1920*1080 (2MP)
Available IR Range	100~110 m Smart IR SMD (Osram-Germany) Technology
D/N Filter	IR Cut Filter Switch (ICR)
Min illumination	Color: 0.002 Lux(AGC on) - B/W: 0.0 Lux(IR on)
Angle of View	H-FOV: 40°~16°, V-FOV: 23°~9°, D-FOV: 46°~19°
Night Vision	Color /IR
Picture Adjust	
Picture Function	140 dB WDR/DWDR, Defog, AWB, EIS, 2D/3D DNR, BLC, HLC, ROI, Anti-flicker, Corridor Mode, Deblur
Shutter Speed	Manual (1/3 ~ 1/100.000)
Image Parameter Control	Off, On, Timing (Adjust 0 ~ 255)
D/N Control	Timing, Auto, Color on, Color off
Image Parameter	Saturation, Brightness, Contrast, Sharpness, Hue
Video / Audio	
Video Compression	H.264+(Ultra H.264), H.265+ (Ultra H.265) MJPEG
Audio Compression	G.711A, G.711U
Frame Rate(60Hz)	90fps@(1920x1080, 1280x960, 1280x720, 704x576)
Transmission Stream	Dual Stream (Code Rate: 256kbps-16mbps)
Network	
Protocols	IPv4/IPv6, ARP, TCP, UDP, RTCP, RTP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, Bonjour, SIP, PPPoE, QoS
Compatibility	Onvif Ver2.6, Profile S/G/Q/T, API, SDK, CGI
Streaming Method	Unicast, Multicast
Web Viewer	IE, Edge, Firefox, Chrome
Smart Device	IOS, Android Phone & Tablet

Function	
Recording	FTP, NVR, CMS, VMS, NAS, SD Card
Record Type	Manual, Motion Detection, Schedule
Alarm Triggers	N/A
Event Action	Email, PTZ, Snapshot, Recording, Alarm Out, Buzzer, Pop up, Show Message
Intelligent Function	N/A
Interface	
Network	1 RJ45 (10M / 100M) Ethernet Port
Audio	Audio Out, Audio In
Alarm	Alarm Out, Alarm In
CVBS	Yes
Power	PoE LAN, DC In
Reset Button	Yes (Optional)
Memory Slot	Yes - Micro SD/SDHC/SDXC Slot (256 Gb Max)
General	
Protection Rating	IP67, IK10, 6KV Surge Protection
Back Box	Yes
Power Supply	DC12V ± 25%
POE Supply	IEEE802.3af - Max 13 Watt
Web Language	English, Persian
Dimension	285*126 mm
Weight	2 Kg
Operation Humidity	Max Up to 95%RH(Non Condensing)
Operation Temp	-40°C ~ +70°C
Guarantee	
Product Guarantee	2 Years Silver Guarantee
MTBF	100K hrs min- MIL-HDBK-217F (25°)
Certificates	EN, CN, FCC, CFR